

Rotary hammer TE 6-CL



APPLICATIONS

- Drilling and hammer drilling in concrete and masonry
- Drilling anchor holes and formwork assembling
- Concrete chiselling and slag removal
- Chiselling of small channel openings into concrete and masonry
- Precision chiselling in masonry

ADVANTAGES

- Built for speed and longevity – re-engineered to deliver higher
- drilling performance from an even more reliable, longer-lasting rotary hammer
- Consistent power output – the 8.5 Amp motor delivers the performance you need to get demanding drilling jobs done faster, even if the power supply fluctuates
- Powerful chiselling performance – with easy adjustment of chisel positioning
- Multi-mode SDS Plus rotary hammer – for hammer drilling, rotary-only drilling and chiselling
- Rapid maintenance – power cords or carbon brushes can be replaced with minimal downtime



Technical data

Rated input power	890 W
Working mode	Hammer drilling, Drilling only, Chiselling, Chisel setting
Optimum drilling diameter in concrete	6 - 16 mm
Drilling diameter range for hammer drill bits	4 - 28 mm
Rotation speed gear 1 under no load	960 rpm
Single impact energy	2.2 J
Full hammering frequency	78 impacts/minute
Triaxial vibration value for hammer drilling into concrete (ah,HD) ¹⁾	15.5 m/s ²
Weight according to EPTA Procedure 01/2003	3.5 kg

¹⁾ according to EN 60745-2-6



Order Now






Package contents

TE 6-CL 230V	Inserts TE CX 1 x Rotary hammer TE 6-CL 230V EU, 1x Hilti Grease, 1x Tool case TE 6-CL	Item Number 2251578
--------------	---	------------------------

Please visit Hilti website for the latest item numbers and related products

Accessories for Rotary Hammers

Ordering designation		TE 2-S	TE 2-M	TE 3-CL	TE 3-ML	TE 6-CL	Sales pack quantity	Item number
Quick-release chuck 13 Drilling in wood or metal		■					1 pc	60208
Chuck spindle TE-C-BFH Adapting a chuck to a tool with TE-C (SDS Plus) connection		■					1 pc	60459
Replacement chuck Chuck for TE-C / TE-CX drill bits with SDS Plus connection end			■				1 pc	273118
Quick-release chuck For insert tools with smooth shanks up to 13mm dia. (no hammering)			■				1 pc	224119
Key-type chuck Drilling in wood or metal			■				1 pc	228434
Angular chuck TE-AC 1 Drilling in concrete and masonry							1 pc	272701
Angular chuck TE-AC 2 Drilling in concrete and masonry					■	■	1 pc	2126158
Dust removal system TE DRS-M Dust module with extraction fan, duct container with filter, depth gauge, end stop, push-fit coupling, packed in a cardboard box							1 pc	2267769
Replacement chuck Chuck for TE-C / TE-CX drill bits with SDS Plus connection end					■	■	1 pc	2123167
Quick release chuck Keyless quick-release chuck for Hilti rotary hammers with chuck interface					■	■	1 pc	2123166
Dust collection device Optional, easily attachable dust collection device (DCD) helps protect the operator from falling dust and fragments when drilling overhead				■	■	■	1 pc	2090706

¹⁾For detailed stock availability and lead time information please contact your Hilti representative.

Please visit Hilti website for the latest item numbers and related products