

**Combihammer TE 70-AVR**

Drilling and Demolition



**Applications**

- Hammer drilling in concrete, masonry and natural stone from 12 - 150 mm in diameter
- Drilling holes for heavy-duty anchors from 20 - 40 mm in diameter
- Breaching and demolition with pointed and flat chisels
- Drilling with high torque in wood and steel

**Advantages**

- High speed of rotation (360 rpm) for extra drilling performance
- Optimized mechanical clutch for maximum torque transfer
- Maximum user comfort thanks to low contact pressure and Active Vibration Reduction (AVR) system for low vibration
- Glass-fibre reinforced casing parts for ruggedness and long life



**Technical data**

<b>Rated input power</b>	1800 W
<b>Triaxial vibration value for hammer drilling into concrete (ah,HD)<sup>1)</sup></b>	10 m/s <sup>2</sup>
<b>A-weighted emission sound pressure level<sup>2)</sup></b>	102 dB (A)
<b>Single impact energy</b>	11.5 J
<b>Rotation speed gear 1 under no load</b>	360 rpm
<b>Full hammering frequency</b>	2760 impacts/minute
<b>Contact force</b>	220 N
<b>Hammer drill bits (optimum dia. range)</b>	20 - 40 mm
<b>Dimensions (LxWxH)</b>	540 x 125 x 305 mm
<b>Weight according to EPTA Procedure 01/2003</b>	8.3 kg

<sup>1)</sup> according to EN 60745-2-6

<sup>2)</sup> according to EN 60745



Order description	Package contents	Sales pack quantity	Item number
TE 70-AVR	1x Combihammer TE 70-AVR, 1x Case	1 pc	2062998

Please visit our website for the latest item numbers and related products.